

Turf Verti-Cutter



Professional Quality **VERTI-CUTTER** Designed for Durability

PTO powered pull unit for verti-cutting, dethatching, renovating and preparation for over seeding.

HARPER.
Goossen

A Division of Harper Industries, Inc.

151 East Hwy. 160 • Harper, KS 67058
1-800-835-1042 • www.goossen.com
email: goosseninfo@deweze.com

- 540 rpm power take-off
- Heavy-duty right angle gear box
- #60 chain drive with shear bolt
- 60" wide swath
- 1 $\frac{1}{2}$ " blade spacing—40 blades
- Blades are 12 ga./10 pt. 12" dia. steel
- Adjustable precision depth control
- Hydraulic lift for transport



VC-60 Plus tandem unit also available



Non-slip chain drive system

Hydraulic lift for transport



540 RPM PTO drive

Distributed by:



SPECIFICATIONS

Model	VC-60, VC-60 Plus
Thatch Swath	60" blade to blade
Blades	(40) 12 ga./10 pt. 12" diameter Corten® Steel
Blade Spacing	1.5"
Blade Shaft	1.5" square steel shaft with heavy-duty jam nut
Blade Shaft Rotation	Forward rotation
Blade Depth	0"–1"
Blade Depth Adjustment	Large jacking bolts on no maintenance skids
Hitch	Adjustable quick pin tag along
Drive	540 RPM PTO to gear box, #60 chain to blade shaft with shear bolt
Required Horse Power	25 to 45 hp
Transport System	Single cylinder with E-Z ram lock, Q.D. from tractor auxiliary valve
Tires	(2) 16 6.50 x 8 turf saver
Frame	All-welded steel construction with three-position adjustable tow bar
Weight	800 lb.
Dimensions	Length: 62" Height: 38" Width: 89"

The manufacturer reserves the right to make changes in engineering, design and specifications or add improvements at any time without notice or obligation.

HARPER
Goossen

A Division of Harper Industries, Inc.

151 E. Hwy. 160 • Harper, KS 67058
1-800-835-1042 • www.goossen.com
email: goosseninfo@deweze.com