

*Worksaver.*

*Designed.  
Engineered.  
Remarkable  
Value.*



**WORKSAVER®**

## **Model ES-1.5, ES-1.5 PKP, ES-33 Seeders**

**Rugged all steel construction for increased durability.**



# Worksaver

## Model ES-1.5, ES-1.5 PKP, ES-33

### MODEL ES-1.5 / ES-1.5 PKP SPECIFICATIONS

Capacity .....	1-1/2 bu.
Hopper construction .....	Steel
Main frame construction .....	Steel
Fan Diameter (in/mm) .....	13 (330 mm)
Fan Drive .....	Electric motor
Electric motor .....	12 volt
Fan speed .....	Variable
Spreading width (ft/m) .....	Up to 30 (9 m)
Hitch requirement ES-1.5 .....	Draw bar mounted
Hitch requirement ES-1.5 PKP.....	2" hitch receiver
Shipping weight ES-1.5 (lb./kg) .....	45 (20 kg)
Shipping weight ES-1.5 PKP (lb./kg) .....	48 / (22 kg)
Product Computer Number ES-1.5 .....	480001
Product Computer Number ES-1.5 PKP .....	480035

### MODEL ES-33 SPECIFICATIONS

Capacity .....	Three (3) bu.
Hopper construction .....	Steel
Main frame construction .....	Steel
Fan Diameter (in/mm) .....	13 (330 mm)
Fan Drive .....	Electric motor
Electric motor .....	12 volt
Fan speed .....	Variable
Spreading width (ft/m) .....	Up to 30 (9 m)
Hitch requirement .....	Draw bar mounted
Shipping weight (lb./kg) .....	70 (32 kg)
Product Computer Number .....	420500

#### USX-3 Optional 3 bu. Hopper extension for ES-33

Product Computer Number ES-1.5 .....	420100
--------------------------------------	--------

- Rugged all steel construction for increased durability.
- Non-corrosive fan for long life and reduced maintenance.
- Positive action seed gate with an adjustable lock scale plate control. Allows quick return to original setting.
- Powered by a standard 12-volt battery for economical seeding.
- Ideal for pickups, jeep and tractors.
- Enables you to sow all grasses, clover, alfalfa, timothy, oats, brome grass, etc.
- Scribed scale plate helps eliminate guesswork on material application.



READ AND UNDERSTAND OPERATOR'S MANUAL BEFORE OPERATION.

Worksaver Inc. has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. Worksaver Inc. is not responsible for differences between specifications or illustrations contained in this publication and the actual equipment.

*Worksaver.*



*Worksaver, Inc.*

P.O. Box 100, Litchfield, IL 62056-0100  
 Phone: 217-324-5973 • Fax: 217-324-3356  
 E-mail: [sales@worksaver.com](mailto:sales@worksaver.com)  
 Web: [www.worksaver.com](http://www.worksaver.com)

Information Provided By:

