



# WORKSAVER®

9 Worksaver Trail - P. O. Box 100 - Litchfield, Illinois 62056-0100  
WEB: <http://www.worksaver.com> E-MAIL: [sales@worksaver.com](mailto:sales@worksaver.com)

## Finishing Mower Rear Discharge

Cut your lawn grooming task down to size with Worksaver high capacity finishing mowers. The models MR-150 (5 ft.) and MR-180 (6 ft.) allow close mowing to shrubs and buildings for faster yard maintenance. Either side may be used for close trimming, which isn't available on side discharge systems.

Rear discharge is standard, which is a huge advantage for eliminating grass buildup in uncut areas, reduces blade wear and fuel cost. High lift blades lift the grass and cut it cleanly discharging it neatly to the rear of mower path. The wide discharge throat provides an unobstructed flow of cut material.

Four caster gauge wheels adjust the cutting height and allows the deck to float with the ground contour. Solid rubber flotation tires are not effected by punctures or tire pressure loss, ensuring level cut every time.

Built rugged for long economical operation, these mowers will leave your lawn areas with that professionally groomed look neighbors will admire.



### FEATURES

- |                            |                              |
|----------------------------|------------------------------|
| ✓ Close mowing             | ✓ Solid wheels and tires     |
| ✓ High capacity cutting    | ✓ Easy height adjustment     |
| ✓ Rear clipping discharge  | ✓ High blade tip speed       |
| ✓ Wide discharge throat    | ✓ Greaseable blade spindle   |
| ✓ 3 Hi-Lift cutting blades | ✓ Quick coupler PTO          |
| ✓ Economical to operate    | ✓ Cast iron gearbox          |
| ✓ Easy maintenance         | ✓ Beveled gears              |
| ✓ Floating 3-pt. hitch     | ✓ Standard safety chainguard |

### SPECIFICATIONS

Model:	MR-150	MR-180
<b>Horsepower:</b>	15 to 30 hp	20 to 40 hp
<b>Cutting Width:</b>	60 inches (5 ft.)	72 inches (6 ft.)
<b>Overall Width:</b>	61 inches	73 inches
<b>Cutting Height:</b>	¾ " minimum to 3-3/4 " maximum	
<b>No. of Blades:</b>	3	3
<b>Blade Size:</b>	2" x 19-7/8" Hi Lift	2-3/8" x 23-7/8" Hi Lift
<b>Blade Tip Speed:</b>	13,480 fpm	14,010fpm
<b>Blade Spindle:</b>	Greaseable - Ball Bearing	
<b>Belt Drive:</b>	V-belt (B-68)	V-belt (B-74)
<b>Deck Thickness:</b>	8 - gauge	
<b>3 pt. Hitch:</b>	Free-Floating Cat. I	
<b>Gauge Wheels:</b>	3" wide x 8" diameter solid rubber - caster	
<b>Wheel Spindle:</b>	Greaseable Sealed Bearings	
<b>Gearbox:</b>	Cast Iron Housing with Beveled Gears	
<b>PTO Driveline:</b>	Quick Coupler Series 2 metric (540 rpm)	
<b>Grass Discharge:</b>	Rear discharge / 35-1/4" wide throat	Rear discharge / 42-3/4 " wide throat
<b>Shipping Weight:</b>	480 lbs.	545 lbs.
<b>Computer #:</b>	652010	652000



**DO NOT RIDE, STAND, OR SERVICE IF ENGINE RUNNING.**



**READ AND UNDERSTAND OPERATOR'S MANUAL BEFORE OPERATION.**

**INFORMATION PROVIDED BY:**