

*Work saver.*

*Designed.  
Engineered.  
Remarkable  
Value.*



## Tandem Disc Harrows

**Ideal for fine finish seedbeds, discs under light cover material. Main frame design incorporates strength and rigidity to work in tough conditions.**






# Worksaver Tandem Disc Harrows

- Engineered simplicity with opposed action disc gangs. Frame design angles disc gangs to eliminate problem of blade overlap and uncut soil.
- Cast iron bearing caps & spools with grease fittings provide long service life.
- Solid 1-inch steel axles & heavy cast spools add weight to the disc gangs for penetration.
- Optional weight frame (# 940325) allows additional weight to be added easily when required.
- High carbon steel disc blades provide excellent cutting.
- 7-1/4" blade spacing produces fine texture level finish.

## TANDEM DISC HARROW SPECIFICATIONS

Model No.	Width (ft.)	Blade Type	# of Blades	Blade Diameter	Item No.	Weight (lbs.)
DH-55-16P	5-1/2 ft.	Plain	16	16"	940354	374 lbs.
DH-55-16N	5-1/2 ft.	Notched	16	16"	940352	362 lbs.
DH-55-16C	5-1/2 ft.	Combination	16	16"	940350	368 lbs.
DH-65-16P	6-1/2 ft.	Plain	20	16"	940364	474 lbs.
DH-65-16N	6-1/2 ft.	Notched	20	16"	940362	462 lbs.
DH-65-16C	6-1/2 ft.	Combination	20	16"	940360	468 lbs.
DH-55-18P	5-1/2 ft.	Plain	16	18"	940359	445 lbs.
DH-55-18N	5-1/2 ft.	Notched	16	18"	940357	440 lbs.
DH-55-18C	5-1/2 ft.	Combination	16	18"	940355	435 lbs.
DH-65-18P	6-1/2 ft.	Plain	20	18"	940369	545 lbs.
DH-65-18N	6-1/2 ft.	Plain	20	18"	940367	540 lbs.
DH-65-18C	6-1/2 ft.	Plain	20	18"	940365	535 lbs.

\*Be sure front of tractor is properly counterbalanced with front-end weights or front-end loader.

-  **READ AND UNDERSTAND OPERATOR'S MANUAL BEFORE OPERATION.**
-  **BE SURE FRONT OF TRACTOR IS PROPERLY COUNTERBALANCED WITH WEIGHTS.**
-  **NEVER ALLOW CHILDREN OR BYSTANDERS AROUND TRACTOR OR DISC WHEN YOU ARE USING EQUIPMENT.**

Worksaver Inc. has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. Worksaver Inc. is not responsible for differences between specifications or illustrations contained in this publication and the actual equipment.



### Worksaver, Inc.

P.O. Box 100, Litchfield, IL 62056-0100  
Phone: 217-324-5973 • Fax: 217-324-3356

E-mail: [sales@worksaver.com](mailto:sales@worksaver.com)

Web: [www.worksaver.com](http://www.worksaver.com)

Information Provided By:

